







DRJ



DRP



DRJ



DRP

Features & Material

- For Only Servo motor, High Torque, High Responsiveness.
- Size Standardization of Shaft diameter from $\varnothing 16 \sim \varnothing 48$.
- Material : S45C

Product NO.	Dimension(mm)							Torque N · m	Thrust kN	Moment of Inertia kg · m ²	Tightening Screw		Max. RPM min ⁻¹	Mass kg
	A	D1	D2	L	L1	L2	P				Size N×M	Torque N · m		
53-16-16	53	16	16	56	60	64	41	98.1	9.8	3.08 × 10 ⁻⁴	4 × M6	17.7	14,500	0.80
53-20-16		20												
53-20-20		20												
53-22-20		22	22											
53-22-22			22											
58-25-20	58	25	20	58	62	66	45	118	9.8	4.18 × 10 ⁻⁴	4 × M6	17.7	12,500	0.87
58-25-22			22											
58-25-25			25											
63-30-25	63	30	25	60	64	68	50.5	157	11.8	6.18 × 10 ⁻⁴	4 × M6	17.7	12,000	1.05
63-30-30			30											
68-35-25	68	35	25	60	64	68	56	186	11.8	8.70 × 10 ⁻⁴	4 × M6	17.7	10,000	1.14
68-35-28			28											
68-35-30			30											
68-35-32			32											
68-35-35			35											
73-35-38	73	38	38	70	74	78	60	226	12.8	1.40 × 10 ⁻³	4 × M6	17.7	9,000	1.51
73-38-42			42											
73-42-42			42											
78-48-48	78	48	48	70	74	78	66	461	18.7	1.85 × 10 ⁻³	6 × M6	17.7	8,000	1.50

Mass and Moment of inertia are measured with max bore size.